



Specifications for Keen K-15R Electrode Oven

- Features:**
- **120V-12 Amp Receptacle to extend power supply to a connected power tool or another Keen rod oven. Create a chain of Keen ovens in the field**

Part Number	010104 (120V – 1 Phase)
Oven Category	Portable - Electrode
Electrode Capacity (LBS)	15 lbs. 18" Electrodes
Electrode Capacity (KGS)	6.8 kgs 45.7cm Electrodes
Standard Voltages	120V AC/DC
Wattage	100W
Temperature Range (°F)	100°F-300°F
Temperature Range (°C)	38°C-149°C
Thermostat	Constant Input
Insulation	1" Thermal Wool
Interior Dimensions (IN)	3.5" Diameter x 18.5"
Interior Dimensions (CM)	8.89cm Diameter x 47cm
External Thermometer	Option Only
Net Weight (LBS)	13 lbs.
Net Weight (KGS)	5.9 kgs.
Shipping Dimensions (IN)	11" x 9" x 23.5"
Shipping Dimensions (CM)	27.94 cm x 22.86 cm x 59.69cm
Shipping Weight (LBS)	16 lbs.
Shipping Weight (KGS)	7.3 kgs.
Power Cord Length	8 ft.
Pilot Light	Standard
CSA Approval	No
UL Approval	No
Accessories	011709 Thermometer Acc.
Replacement Parts	301021 Element
Equal or Similar to:	Phoenix Type 1 (10 lbs. Capacity)
Similar Keen Ovens	K-5, K-15, K-15W/T, K-50

Keen K-15 Series Repair Parts List

Element 120V	Element W/T 120V	Element W/T 240V	Power Cord	Chest Handle
301021	301019	301020	301155	430103

Bottom Cover	Thermost 120V	W/T 120V	W/T 240V	Rod Lifter	Strain	Pilot Light
100103	301024	301024	301024	100107	301043	301085