



Specifications for Keen K-MPO Storage Oven

Part Number	010706 – (120V – 1 Phase)
010710 – (480V – 3 Phase)	010707 - (240V – 1 Phase)
Oven Category	Floor - Mixed Use
Electrode Capacity (LBS) Wire Capacity (# of Spools)	600 lbs. 18" Rods 6/12" Wire Spools
Electrode Capacity (KGS) Wire Capacity (# of Spools)	272.16 kgs. 45.7cm Rods 6/30.4cm Wire Spools
Standard Voltages Available	120V, 240V, 480V
Wattage	2000W
Temperature Range (°F)	150-550°F
Temperature Range (°C)	66-288°C
Thermostat	Dial Adjustable
Insulation	2" Thermal Wool
Interior Dimensions (IN)	27.5" x 20.5" x 40"
Interior Dimensions (CM)	68.58cm x 52.07cm x 101.60cm
External Thermometer	Standard
Net Weight (LBS)	300 lbs.
Net Weight (KGS)	136.08 kgs.
Shipping Dimensions (IN)	36" x 42" x 56"
Shipping Dimensions (CM)	91.44cm x 106.68cm x 142.24cm
Shipping Weight (LBS)	390 lbs
Shipping Weight (KGS)	176.9 kgs.
Power Cord Length	8 ft.
Pilot Light	Standard
CSA Approval	No
UL Approval	No
Accessories	None Available
Equal or Similar to:	Phoenix Drywire (24/12" Spools)
Similar Keen Ovens	K-900, K-1000, K-1000M&T

Keen K-MPO Repair Parts List

Shelf Assembly	Name Plate	Handy Box	Door Pull	Cord (120V)	Element 120V
N/A	450103	301033	430102	301014	301023
Cord (240V)	Strain Relief	Strain 240V	Pull Catch	Pilot	Thermostat
301018	301041 (120V)	301043	430106	301085	31038
Leveler Bolts	Strain Relief 480V	Handy Box	Door Pull	Element 480V	Element 240V
400109	301049	301038	430102	301029	301026